





SB3 1200 x 1000 x 790 mm / 610 l





Art. no. 81940891

Technical data			
Dimensions L x W x H (mm)	1200 X 1000 X 790		
Weight (kg)	38.5		
Volume (I)	610		
Material	PE		
Load capacity (kg)	Stacking Load 5000 kg	Holding Capacity 700 kg	Dynamic Load 1200 kg

Characteristics

Colour: light grey Manufactured in one piece Runners: 9 feet

Stackable

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

El contenedor se corresponde con los estándares DIN EN 13626 y DIN EN ISO 12048

Options


Drain port Solid walls / base 3 Runners

Loading quantities (Pcs / Approximate amount)


Container	Container 20': 30 Container 40': –	Container 40' High Cube: 84 Conventional trailer 45' high cube container: 104
Truck	MEGA-Trailer: 130	lumbo: 140-150



 $Customised\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$









- *1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- *2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- *3 Stacking Load: at a room temperature of approx. 20°C. Dynamic Load: on a forklift with an evenly distributed load at a room temperature of approx. 20°C.