





**CB3** 





#### Art. no. 83281808

Technical data			
Dimensions L x W x H (mm)	1200 X 1000 X 740		
Weight (kg)	36.5		
Volume (I)	610		
Material* <sup>2</sup>	PE		
Load capacity (kg)*3	Stacking Load 5000 kg	Holding Capacity 700 kg	bynamic Load 1200 kg

## Characteristics

Colour: basalt grey Manufactured in one piece Runners: 3, unwelded

Stackable

Temperature stability: -30 °C to +40 °C, briefly up to +90 °C

Resistant to most chemicals and cleaning agents

Food-safe. HACCP compliant

Container is based on DIN EN 13626 and DIN EN ISO 12048

8

## Options

Transponder (RFID) Lid

# Loading quantities (Pcs / Approximate amount)

Container	Container 20': <b>40</b> Container 40': –	Container 40' High Cube: <b>106</b> Conventional trailer 45' high cube container: <b>104</b>
Truck	MEGA-Trailer: 130	Jumbo: <b>140-150</b>

#### Labelling

 $Customised\ printing\ and\ numbering\ available\ on\ request\ depending\ on\ quantity.\ Position\ upon\ consultation.$ 









- \*1 All technical data include characteristic features, which have been tested under specially defined conditions. Varying data may result from different conditions of usage such as loading method, prevailing temperature and length of storage time. All data and specified information are subject to change without notice. Our service team is pleased to be at your disposal to check the special requirements of your individual application.
- \*2 Our service team is pleased to be at your disposal if you require exact information about material compositions.
- \*3 Stacking Load: With a maximum stacking height of 6 boxes (5 on 1 stacking) and evenly distributed load at approx. 20 °C. Dynamic Load: On a forklift with an evenly distributed load at a room temperature of approx. 20 °C.